















Equipment	Interior Dimensions	Door Opening	Top Opening	Tare Weight	Cubic Capacity	Payload*
20'Dry Freight 	L 5,919mm W 2,340mm H 2,380mm	W 2,286mm H 2,278mm		1,900 kg 4,189 lbs	33.0 cbm 1,165 cu.ft	22,100 kg 48,721 lbs
40'Dry Freight 	L 12,045mm W 2,309mm H 2,379mm	W 2,280mm H 2,278mm		3,084 kg 6,799 lbs	67.3 cbm 2,377 cu.ft	27,396 kg 60,397 lbs
40'High Cube Dry 	L 12,056mm W 2,347mm H 2,684mm	W 2,340mm H 2,585mm		2,900 kg 6,393 lbs	76.0 cbm 2,684 cu.ft	29,600 kg 65,256 lbs
45'High Cube Dry 	L 13,582mm W 2,347mm H 2,690mm	W 2,340mm H 2,585mm		3,900 kg 8,598 lbs	85.7 cbm 3,026 cu.ft	28,600 kg 63,052 lbs
20'Reefer 	L 5,428mm W 2,266mm H 2,240mm	W 2,286mm H 2,188mm		2,940 kg 6,482 lbs	27.5 cbm 971 cu.ft	24,060 kg 53,043 lbs
40'Reefer 	L 11,207mm W 2,246mm H 2,183mm	W 2,216mm H 2,118mm		4,840 kg 10,670 lbs	54.9 cbm 1,939 cu.ft	25,640 kg 56,526 lbs
40'High Cube Reefer 	L 11,628mm W 2,294mm H 2,509mm	W 2,290mm H 2,535mm		4,430 kg 9,766 lbs	66.9 cbm 2,363 cu.ft	28,070 kg 61,883 lbs
45'High Cube Reefer 	L 13,102mm W 2,294mm H 2,509mm	W 2,290mm H 2,535mm		5,200 kg 11,464 lbs	75.4 cbm 2,663 cu.ft	27,300 kg 60,186 lbs
20'Open Top 	L 5,919mm W 2,340mm H 2,286mm	W 2,286mm H 2,251mm	L 5,425mm W 2,222mm	2,174 kg 4,793 lbs	31.6 cbm 1.116 cu.ft	21,826 kg 48,117 lbs
40'Open Top 	L 12,043mm W 2,340mm H 2,272mm	W 2,279mm H 2,278mm	L 11,585mm W 2,162mm	4,300 kg 9,480 lbs	64.0 cbm 2,260 cu.ft	26,181 kg 57,720 lbs
20'Flat Rack 	L 5,662mm W 2,438mm H 2,327mm			2,530 kg 5,578 lbs		21,470 kg 47,333 lbs
20'Collapsible Flat Rack 	L 5,946mm W 2,126mm H 2,233mm			2,900 kg 6,393 lbs		27,100 kg 59,745 lbs
40'Flat Rack 	L 12,080mm W 2,438mm H 2,103mm			5,480 kg 12,081 lbs		25,000 kg 55,115 lbs
40'Artificial Tweendeck 	L 12,065mm W 2,216mm			5,400 kg 11,905 lbs		39,000 kg 85,979 lbs